

DOUBLE SIDED TAPE

TECHNICAL DATA SHEET

PUBLISHED 19 AUGUST 2024

PRODUCT DESCRIPTION

LYSAGHT® Double Sided Tape is a white, double-sided, acrylic tape with high bonding properties.

PRODUCT APPLICATION

Used for the adhesion of flexible building membranes to steel framing prior to installation of cladding.

ASSOCIATED PRODUCTS

- LYSAGHT COREGUARD™ Class 4 Breathable Membrane
- Jointing Tape



PRODUCT SPECIFICATIONS

Roll Size	25mm x 100m
Colour	White

TECHNICAL DATA

Adhesive Carrier	Polyester Scrim
Adhesive System	Acrylic Dispersion
Release Liner	Silicone-Coated Filmic Liner, White
Thickness, Without Liner	0.22 – 0.24mm
Peel Adhesion	≥ 30 N/25mm
Sheer Adhesion	100g / 625mm²
Application Temperature	+5°C recommended, processable from -10°C
Temperature Resistance	-30°C to +100°C
Tack	Excellent
Condensation Water Resistance	High
Ageing Resistance	Very high

STORAGE & HANDLING

Store product out of direct sunlight in a cool, dry place between 5-25°C. Product should not be exposed to chemicals or left in direct contact with soil.

PRODUCT DESCRIPTIONS

All descriptions, specifications, illustrations, drawings, data, dimensions, and weights contained in this publication and websites containing information from Lysaght are approximations only. They are intended by Lysaght to be a general description for information and identification purposes and do not create a sale by description. Lysaght reserves the right at any time to:

- a) Supply goods with such minor modifications from its drawings and specifications as it sees fit, and
- b) Alter specifications shown in its publications and websites to reflect changes made after the date of publication.

DISCLAIMER, WARRANTIES AND LIMITATIONS OF LIABILITY

- This publication is intended to be an aid for all trades and professionals involved with specifying and installing LYSAGHT® products and not be a substitute for professional judgement.
- Terms and conditions of sale are available at lysaght.com/terms
- Except to the extent to which liability may not lawfully be excluded or limited, BlueScope Steel Limited will not be under or incur any liability to you for any direct or indirect loss or damage (including, without limitation, consequential loss or damage such as loss of profit or anticipated profit, loss of use, damage to goodwill and loss due to delay) however caused (including, without limitation, breach of contract, negligence and/or breach of statute), which you may suffer or incur in connection with this publication.

FOR DETAILED PRODUCT INFORMATION MANUALS AND PROJECT CASE STUDIES VISIT:

LYSAGHT.COM