LONGLINE 305[®] WA



CYCLONIC AREAS ADDENDUM

This document is to be read in conjunction with the LYSAGHT® Cyclonic Area Design Manual current at the time of publication.

The information is based on full-scale testing with low-high-low pressure sequence for cyclonic areas.

LONGLINE 305® WA STRENGTH LIMIT STATE WIND PRESSURE CAPACITIES (KPA) 0.70MM BMT


Span (mm)	Single & End	Internal
600	7.55	8.60
900	5.50	6.60
1200	3.95	5.05
1500	2.90	3.85
1800	2.45	3.00



1 clip per sheet per support, 2 fasteners per clip. Fasteners Buildex #10-16x16 Metal Teks $^{\oplus}$ Wafer Head or equivalent.



- 1. The pressures are applicable when the cladding is fixed to a minimum of 1.5mm BMT steel.
- 2. More detailed information (including overhangs) are available in the LONGLINE 305® WA brochure.



DISCLAIMER, WARRANTIES AND LIMITATION OF LIABILITY

This publication is intended to be an aid for all trades and professionals involved with specifying and installing lysaght products and not to be a substitute for professional judgement.

Terms and conditions of sale available at local Lysaght sales offices.

Except to the extent to which liability may not lawfully be excluded or limited, BlueScope Steel Limited will not be under or incur any liability to you for any direct or indirect loss or damage (including, without limitation, consequential loss or damage such as loss of profit or anticipated profit, loss of use, damage to goodwill and loss due to delay) however caused (including, without limitation, breach of contract, negligence and/or breach of statute), which you may suffer or incur in connection with this publication.

FOR DETAILED PRODUCT INFORMATION, MANUALS AND PROJECT CASE STUDIES VISIT:

WWW.LYSAGHT.COM

LYSAGHT® and LONGLINE 305® are registered trademarks of BlueScope Steel Limited, ABN 16 000 011 058. Tek® is a registered trademark of ITW Buildex.

The LYSAGHT® range of products is exclusively made by or for BlueScope Steel Limited trading as Lysaght.
© BlueScope Steel Limited September 2022 ABN 16 000 011 058.
All rights reserved.

