

FACADES

NATIONAL CONSTRUCTION CODE (NCC) COMPLIANCE BULLETIN



MARCH 2025 | This version supersedes all previous issues.



THIS BULLETIN DETAILS RELEVANT NCC OF AUSTRALIA COMPLIANCE INFORMATION RELEVANT TO LYSAGHT® FACADE PRODUCTS

- HORIZON®

LYSAGHT® – YOUR GUARANTEE OF COMPLIANCE

The National Construction Code of Australia (NCC) details the minimum necessary requirements for safety, health, amenity and sustainability that need to be met in the design and construction of new buildings (and new building work in existing buildings) throughout Australia.

Using products that do not conform to the NCC requirements can leave installers, builders and suppliers liable for cost of replacement, rectification and consequential damages.

Lysaght's range of Australian-made steel building products has been developed, tested and manufactured to not only meet our country's demanding climatic and geographic requirements but also to provide building designers, builders and owners

with the confidence that comes from using guaranteed compliant products.

The compliance statements overleaf outline compliance of Lysaght's range of facade products with both the National Construction Code of Australia and the relevant Australian Standards for both Residential and Non-residential buildings.

NATIONAL CONSTRUCTION CODE OF AUSTRALIA (NCC 2022) COMPLIANCE STATEMENT

LYSAGHT® FACADE PRODUCT RANGE



Issuing entity:		BlueScope Steel Limited trading as Lysaght				
Issue Date		March 2025				
Application		Walling for Class 2 to 9 Buildings (Vol 1 of the NCC) and for Class 1 and 10 Buildings (Vol 2 of the NCC)				
Scope of Use		All products noted below may be used for wall and rain screen façade applications when designed using the individual construction manuals available for each product, accessible at lysaght.com				
Product Brand		LYSAGHT®				
PRODUCTS¹	Walling only	HORIZON® Facade panels				
Base Metal Brand		COLORBOND® steel	COLORBOND® steel Matt	COLORBOND® Metallic steel	COLORBOND® Ultra steel	ZINCALUME® steel backing skin
Typical Environments		For low to high corrosive environments >200m from breaking surf >100m from calm marine	For low to high corrosive environments >200m from breaking surf >100m from calm marine	For high to very high corrosive environments >100m from breaking surf >0m from calm marine	For high to very high corrosive environments >100m from breaking surf >0m from calm marine	For low to high corrosive environments >200m from breaking surf >100m from calm marine
Base Metal Thickness Range	Walling	0.55mm – 0.75mm	0.55mm – 0.75mm	0.55mm – 0.75mm	0.55mm – 0.75mm	0.55mm – 0.75mm
Minimum Yield Strength		300 MPa	300 MPa	300 MPa	300 MPa	300 MPa
Coating		AM100	AM100	AM100	AM150	AM125
Paint²		100 g/m² minimum metallic coating mass, (aluminium/zinc/magnesium alloy) with Activate® technology to AS 1397	100 g/m² minimum metallic coating mass, (aluminium/zinc/magnesium alloy) with Activate® technology to AS 1397	100 g/m² minimum metallic coating mass, (aluminium/zinc/magnesium alloy) with Activate® technology to AS 1397	150 g/m² minimum metallic coating mass, (aluminium/zinc/magnesium alloy) with Activate® technology to AS 1397	125 g/m² minimum metallic coating mass, (aluminium/zinc/magnesium alloy) with Activate® technology to AS 1397
Paint²		Paint coating to AS 2728 with Thermatech® solar reflectance technology	Paint coating to AS 2728 with Thermatech® solar reflectance technology	Paint coating to AS 2728 Type 3	Paint coating to AS 2728 Type 4 with Thermatech® solar reflectance technology	N/A
Solar Absorptance Value Range		0.28 – 0.95	0.35 – 0.79	0.34 – 0.94	0.33 – 0.73	N/A
Warranty³	Walling	Up to 15 years	Up to 15 years	Up to 15 years	Up to 15 years	Up to 15 years
Combustibility		The HORIZON® panel meets the requirements of NCC 2022, Volume 1 C2D10 (6) (e) - Pre-finished metal sheeting having a combustible surface finish not exceeding 1mm thickness and where Spread-of-Flame index of the product is not greater than 0. The product has been tested to AS/NZS 1530.3 (CSIRO Report No: FNE12929-A) and achieved a Spread of Flame Index of 0. The adhesive used for the stiffener meets the non-combustibility exemption requirements of NCC 2022 Volume 1 C2D10(4)(p), which applies only to adhesives and tapes associated with stiffeners that may be installed to prevent buckling, bowing or distortion of a cladding material.				
Weather Proofing Performance		The HORIZON™ panel meets the requirement of NCC 2022 DTS Compliance provisions for weather proofing, in accordance to NCC 2022 Volume 1 F3D5 (1c) and NCC 2022 Volume 2 H1D7(5) -AS 1562.1 for metal wall cladding.				
Acceptable Construction Manuals		HORIZON® Facade panels Design and installation Manual Non Cyclonic LYSAGHT® Architectural Detailing and Flashing Manual for Architects and Detailing Professionals LYSAGHT® Product Advisory Bulletins Guides				
Australian Standards Compliance	Limit State Capacities for Strength and Serviceability have been determined from testing at NATA accredited facilities in compliance with the following standards:	AS 1562.1-2018 - Design and installation of sheet roof and wall cladding - Part 1: Metal AS 4040.0-1992 - Methods of testing sheet roof and wall cladding AS 4040.2-1992 (Rec: 2016, Amd 1:2018) - Methods of testing sheet roof and wall cladding, Part 2: Resistance to wind pressures for non-cyclone regions AS 4040.3:2018 - Methods of testing sheet roof and wall cladding, Method 3: Resistance to wind pressures for cyclone regions				
	BlueScope coated steel products have been determined to be compliant with the following standards:	AS 1397:2021 - Continuous hot-dip metallic coated steel sheet and strip - Coatings of zinc and zinc alloyed with aluminium and magnesium AS/NZS 2728:2013 - Prefinished/prepainted sheet metal products for interior/exterior building applications - Performance requirements AS 1397:2021 - Defines the coating types and classes and steel grades for hot-dip metallic coated steel. LYSAGHT® product coating compliance is nominated at "Coating" above. Product made to other standards may not meet the ductility or strength requirements assumed by design standards or the minimum coating class requirements critical to building durability. AS/NZS 2728:2013 - Specifies requirements for the physical properties and long-term durability of pre-finished/pre-painted sheet metal products. LYSAGHT® pre-painted compliance is nominated at "Paint" above for Performance requirement 1.3.1 Metal products Hot dipped metallic coated steel (types Z, ZM, AZ, AM) complying with AS 1397, stainless steel, aluminium, or aluminium alloy in the form of sheet, coil, or strip.				
Compliance with the deemed-to-satisfy provision of the NCC		NCC Volume 1 - For class 2 to 9 Buildings • Section F3D1 Deemed-to-Satisfy Provisions • F3D5 Wall cladding (c) Metal wall cladding : AS1562.1 NCC Volume 2 - For class 1 and 10 Buildings • H1D7(5)- AS 1562.1 for Metal wall cladding Published Capacity tables in reference manuals above are suitable to determine structural adequacy and serviceability of nominated products for individual projects referencing the following Australian Standards and NCC requirements: • NCC, Volume 1, Section B - Structure, Part B1 -Structural provisions (Deemed-to-Satisfy Provisions), Clause B1D2 Resistance to actions, and Clause B1D3 Determination of individual actions AS/NZS 1170.0:2002 - Structural design actions - Part 0: General principles AS/NZS 1170.1:2002 - Structural design actions Part 1: Permanent , Imposed and other actions AS/NZS 1170.2:2021- Structural design actions Part 2: Wind actions				

- Notes:**
1. Not all products are available in all materials and finishes. Not all products are available in all regions. Visit lysaght.com for more information.
 2. Thermatech® solar reflectance technology is incorporated in the standard COLORBOND® steel colour range, excluding colour Night Sky®.
 3. Warranties are subject to application and eligibility criteria. For full terms and conditions and warranty eligibility for BlueScope steel products visit warranties.bluescopesteel.com.au.
 4. NATA – National Association of Testing Authorities.

UNDERSTANDING COMPLIANCE

The National Construction Code (NCC) outlines deemed-to-satisfy requirements for metal claddings based on compliance to Australian Standards. Whilst the applicable Australian Standards differ between Residential and Non-Residential buildings, the underlying common tenants are;

- a) That installed metal products must be able to meet expected Structural, Wind and Installation loads as per the Australian Standards,
- b) That installed metal products must be sufficiently durable to meet the amenity and sustainability requirements of the Australian Standards.

To determine a metal cladding's capacities and ability to comply with Australian design standards, metal cladding products must be tested in accordance with AS 4040.0. Metal cladding products that cannot demonstrate testing to AS 4040.0 and compliance with other relevant Australian Standards do not meet the deemed-to-comply provisions of the NCC.

LYSAGHT® steel building products have been tested in Lysaght's own NATA-accredited testing facility to meet all relevant Australian Standards as outlined in this document.

STATEMENT OF PRODUCT CONFORMANCE

This document confirms that the structural design capacity tables for LYSAGHT® Wall Cladding products included in the Acceptable Construction Manuals referenced in this bulletin have been prepared in accordance with the relevant Australian Standards & Deemed to satisfy provisions of NCC 2022 as referenced below.

Designs utilising data from these reference documents can form part of a structurally adequate assembly, subject to the following conditions:

- Installation and construction of roofing and walling products is in accordance with the Acceptable Construction Manuals referenced in this bulletin and accepted good construction practice.

CHAIN OF RESPONSIBILITY

It is the primary responsibility of each person in the value chain, from designer to supplier to installer to builder to ensure that products used on a building are;

- a) Suitable for the intended use, and;
- b) Comply with relevant Australian Standards and NCC provisions. Increasingly regulatory authorities are requiring documentary evidence of a products compliance to the requirements of the NCC.

Recent Queensland legislation goes further placing an onus on all members in the chain of responsibility to report the use of any non-conforming product.

DISCLAIMER, WARRANTIES AND LIMITATIONS OF LIABILITY

This publication is intended to be an aid for all trades and professionals involved with specifying and installing LYSAGHT® products and not be a substitute for professional judgement.

Terms and conditions of sale are available at lysaght.com/terms

Except to the extent to which liability may not lawfully be excluded or limited, BlueScope Steel Limited will not be under or incur any liability to you for any direct or indirect loss or damage (including, without limitation, consequential loss or damage such as loss of profit or anticipated profit, loss of use, damage to goodwill and loss due to delay) however caused (including, without limitation, breach of contract, negligence and/or breach of statute), which you may suffer or incur in connection with this publication.

INSIDE OUR BRANDS

Lysaght's range of steel building products are manufactured using Australia's leading coated steel materials.

COLORBOND® prepainted steel and ZINCALUME® metallic coated steel are supplied to Lysaght in large coils. Lysaght then shapes and forms these materials (through the process known as rollforming) into our range of roofing profiles, gutters, fascia and downpipes, plus products for fencing systems and home additions such as verandahs, patios and carport.

YOUR COMPLIANCE CHECKLIST

- Fully specify LYSAGHT® Profile, Finish & Coating class
- Check all details when you receive order confirmation
- On-Site - check delivery docket and product branding

FOR DETAILED PRODUCT INFORMATION,
MANUALS AND PROJECT CASE STUDIES VISIT:

[WWW.LYSAGHT.COM](https://www.lysaght.com)

COLORBOND®, ZINCALUME®, Thermatech®, LYSAGHT® and ® product names are registered trademarks of BlueScope Steel Limited and ™ product names are trademarks of BlueScope Steel Limited.
© 2024 BlueScope Steel Limited. ABN 16 000 011 058. All rights reserved

INSPIRATION TO BUILD BETTER

LYSAGHT