

Jointing Tape

Technical Data Sheet

Published 19 August 2024

Product Description

Fielders® Jointing Tape is a black, single-sided, acrylic tape with high UV resistance.

Product Application

Used to seal overlapping sections of flexible building membranes, along with joints and penetrations.

The tape is reinforced with scrim to ensure maximum strength and durability across the lifetime of the bond.

Associated Products

- Fielders ShieldGuard™ Class 4 Breathable Membrane
- Double Sided Tape



Product Specifications

Roll Size	60mm x 25m
Colour	Black

Technical Data

Adhesive Carrier	LDPEco Film, Black, Reinforced with Scrim
Adhesive System	Acrylic Dispersion
Release Liner	Silicone-Coated Paper, Brown
Thickness, Without Liner	0.30 - 0.33mm
Peel Adhesion	≥ 35 N/25mm
Elongation	≥ 25 N/25mm; 300 %
Application Temperature	+5°C recommended, processable from -10°C
Temperature Resistance	-30°C to +100°C
Tack	Excellent
Condensation Water Resistance	High
Ageing Resistance	2 Years UV Resistance (Exposed)

Storage & Handling

Store product out of direct sunlight in a cool, dry place between 5-25°C. Product should not be exposed to chemicals or left in direct contact with soil.

Product Descriptions

All descriptions, specifications, illustrations, drawings, data, dimensions, and weights contained in this publication and websites containing information from Fielders are approximations only. They are intended by Fielders to be a general description for information and identification purposes and do not create a sale by description. Fielders reserves the right at any time to:

- a) Supply goods with such minor modifications from its drawings and specifications as it sees fit, and
- b) Alter specifications shown in its publications and websites to reflect changes made after the date of publication.

Disclaimer, Warranties and Limitations Of Liability

- This publication is intended to be an aid for all trades and professionals involved with specifying and installing Fielders® products and not be a substitute for professional judgement.
- Terms and conditions of sale are available at fielders.com.au/legals/
- Except to the extent to which liability may not lawfully be excluded or limited, BlueScope Steel Limited will not be under or incur any liability to you for any direct or indirect loss or damage (including, without limitation, consequential loss or damage such as loss of profit or anticipated profit, loss of use, damage to goodwill and loss due to delay) however caused (including, without limitation, breach of contract, negligence and/or breach of statute), which you may suffer or incur in connection with this publication.

For detailed product information, manuals and project case studies visit:

fielders.com.au

Fielders® and ® product names are registered trademarks of BlueScope Steel Limited and ™ product names are trademarks of BlueScope Steel Limited. © 2024 BlueScope Steel Limited. ABN 16 000 011 058. All rights reserved.

